

PRODUCT DATASHEET

LED Value Batten 600 mm 10 W 4000 K

LED VALUE BATTEN | LED batten luminaires for wall and ceiling mounting



AREAS OF APPLICATION

- Indoor applications
- Ceiling and wall surface mounting
- Corridors, stairwells, basements
- General indoor illumination

PRODUCT BENEFITS

- Excellent price/performance ratio
- High energy savings compared to luminaires that use conventional light sources
- Functional and minimalistic design

PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- Wall and ceiling batten luminaire
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime: up to 30,000 h
- Color temperature: 4,000 K
- Luminaire efficacy: up to 100 lm/W
- Lengths available: 0.6 m, 1.2 m, 1.5 m



TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	1000 lm
Luminous efficacy	100 lm/W

Dimensions & weight



Length	634.0 mm
Width	29.0 mm
Height	44.0 mm
Product weight	225.00 g

Colors & materials

Body material	Aluminum
Housing color	Silver
Product color	Silver
Housing color	Silver
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
----------------------------------	--------------

Temperature range in operation	-20...+40 °C
--------------------------------	--------------

Lifespan

Number of switching cycles	25000
Rated lamp life time	30000 h

Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall
Mercury content	0.0 mg

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/EAC/REACH/RoHS
ErP For end-consumer	yes
EEL of included LED module	A++/A+/A

Logistical data

ErP For end-consumer	yes
----------------------	-----

EQUIPMENT / ACCESSORIES

- Mounting clips included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075268142	Folding carton box 1	44 mm x 30 mm x 634 mm	234.00 g	0.84 dm ³
4058075268159	Shipping carton box 20	660 mm x 165 mm x 205 mm	5036.00 g	22.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.