

PRODUCT DATASHEETSubMARINE Integrated 600 18 W 4000 K

SUBMARINE Integrated | Damp-proof luminaires with integrated LED module

AREAS OF APPLICATION

- Basements, garages, warehouses



PRODUCT BENEFITS

- Easy and quick installation
- Very homogenous light
- Extremely bright

PRODUCT FEATURES

- Dust-protected and jet-proof (IP65)
- Not dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	18.00 W	
Operating mode	Integrated LED driver	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

Photometrical data

Color temperature	4000 K	
Color rendering index Ra	>80	
Light color (designation)	Cool White	
Luminous flux	1500 lm	
Luminous efficacy	83 lm/W	

Dimensions & weight



Length	590.0 mm
Width	86.0 mm
Height	66.0 mm
Product weight	670.00 g

Colors & materials

Body material Polycarbonate (PC)	
Product color	Gray
Housing color	Gray

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Temperature range in operation	-20+40 °C

Lifespan

Rated lamp life time	30000 h
----------------------	---------

Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall
Mercury content	0.0 mg

Capabilities

Dimmable	No	
Type of connection	Terminal, 2-Pole (L, N)	
LED module replaceable	Not replaceable	

Certificates & standards

Protection class	II	
Type of protection	IP65	
Standards	CE/EAC/REACH/RoHS	
EEI of included LED module	A++/A+/A	

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075260351	Folding carton box 1	89 mm x 620 mm x 69 mm	764.00 g	3.81 dm ³
4058075260368	Shipping carton box 8	640 mm x 200 mm x 304 mm	6606.00 g	38.91 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.