

PRODUCT DATASHEET

SubMARINE Integrated 1500 48 W 4000 K

SUBMARINE Integrated | Damp-proof luminaires with integrated LED module



AREAS OF APPLICATION

- Basements, garages, warehouses

PRODUCT BENEFITS

- Easy and quick installation
- Very homogenous light
- Extremely bright

PRODUCT FEATURES

- Dust-protected and jet-proof (IP65)
- Not dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	48.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	4000 lm
Luminous efficacy	60 lm/W

Dimensions & weight



Length	1480 mm
Width	86.0 mm
Height	72.0 mm
Product weight	1580.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	Gray
Housing color	Gray

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

Lifespan

Rated lamp life time	30000 h
----------------------	---------

Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall
Mercury content	0.0 mg

Capabilities

Dimmable	No
Type of connection	Terminal, 2-Pole (L, N)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP65
Standards	CE/EAC/REACH/RoHS
EEL of included LED module	A++/A+/A

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075260498	Folding carton box 1	89 mm x 1510 mm x 75 mm	1790.00 g	10.08 dm ³
4058075260504	Shipping carton box 8	1530 mm x 200 mm x 328 mm	15391.00 g	100.37 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.