

PRODUCT DATASHEET ENDURA CLASSIC Trad Alu 330 E27 GD

ENDURA CLASSIC TRADITION ALU | Timeless lantern shape with aluminum housing



AREAS OF APPLICATION

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- High flexibility in the choice of the light source thanks to E27 base
- Suitable for smart applications thanks to compatibility with Smart + lamps from LEDVANCE
- Easy and quick installation

PRODUCT FEATURES

- Die-cast aluminum housing
- Diffuser made of clear polycarbonate
- Available with and without motion sensor
- Available as wall and bollard luminaires




TECHNICAL DATA

Electrical data

Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Dimensions & weight



Length	170.0 mm
Width	170.0 mm
Height	325.0 mm
Product weight	555.00 g

Colors & materials

Body material	Aluminum
Product color	Black/Gold
Housing color	Black/Gold

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Additional product data

Mounting type	Standing
Mounting location	Floor
Equipped with lamp	No

Capabilities

Dimmable	No
Type of connection	Screw terminal
Holder designation	E27

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075206342	Folding carton box 1	194 mm x 194 mm x 346 mm	622.00 g	13.02 dm³
4058075206359	Shipping carton box 4	403 mm x 403 mm x 365 mm	3238.00 g	59.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.