

# **PRODUCT DATASHEET**ENDURA FLOOD Sensor 10 W 4000 K DG

**ENDURA FLOOD Sensor Cool White | Outdoor sensor luminaires in 4000K** 



#### **AREAS OF APPLICATION**

- Outdoor use (IP44)
- Replacement for floodlights with halogen lamps
- Garages
- Building facades

#### **PRODUCT BENEFITS**

- Optimized weight and size due to compact design
- Energy savings of up to 80 % compared to halogen lamp floodlights
- Semi-frosted, tempered glass cover for uniform illumination

#### **PRODUCT FEATURES**

- Very bright and functional outdoor LED luminaires
- Symmetrical beam angle: 110° x 110°
- Mounting bracket for up to 180° tilting
- Ambient temperature in operation: -10...+40 °C
- Connection via 1 m cable, wiring required
- Adjustable IR daylight and motion sensor with a detection range of up to 9 m



# **TECHNICAL DATA**

## Electrical data

Nominal wattage	10.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz


## Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	800 lm
Luminous efficacy	80 lm/W

#### Luminaire sensor data

Type of sensor	Light / Motion	
Sensor technology Passive infrared (PIR)		
Sensor detection angle 120 °		
Detection range of motion sensor	29 m	
<b>Detection threshold of daylight sensor</b> 202000 lx		
Sensor controlled switching time	10 s10 min	

# Dimensions & weight



Length	168.0 mm
Width	108.0 mm
Height	63.0 mm
Product weight	380.00 g

#### Colors & materials

Body material	Aluminum
Product color	Dark gray
Housing color	Dark gray

## Temperatures & operating conditions

Ambient temperature range	-10+40 °C

#### Lifespan

Number of switching cycles	100000

#### Additional product data

Mounting type	Surface
Mounting location	Wall

## Capabilities

Dimmable	No
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

#### Certificates & standards

Protection class	T .
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075292192	Folding carton box 1	84 mm x 117 mm x 182 mm	426.00 g	1.79 dm <sup>3</sup>
4058075292208	Shipping carton box 8	348 mm x 245 mm x 200 mm	4210.00 g	17.05 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.