

PRODUCT DATASHEET

SUBMARINE 1X16 W 120 4000 K

SUBMARINE | Damp-proof luminaires for LED tubes

AREAS OF APPLICATION

- Basements, garages, warehouses
- For indoor use only



PRODUCT BENEFITS

- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Easy installation thanks to improved space for mounting brackets and easy to open tray
- Quick and easy lamp replacement
- Extremely break resistant. SubstiTUBE Star PC LED-Tube included
- Good, even illumination

PRODUCT FEATURES

- Damp-proof luminaire with LED tube for mains voltage operation
- Durable and energy-saving LED luminaire
- Dust-protected and jet-proof (IP65)
- Mercury-free and RoHS compliant
- M20 cable gland for 8-12 mm cables
- Not dimmable



TECHNICAL DATA


Electrical data

Nominal wattage	16.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Max. power consumption	16 W

Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	1550 lm
Luminous efficacy	96 lm/W

Dimensions & weight



Length	1261 mm
Width	67.0 mm
Height	75.0 mm
Product weight	1250.00 g

Colors & materials

Body material	Acrylonitrile butadiene styrene (ABS)
Product color	Gray
Housing color	Gray
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+35 °C
Temperature range in operation	-20...+35 °C

Lifespan

Number of switching cycles	100000
Lifespan	30000 h
Rated lamp life time	30000 h

Additional product data

Mounting type	Surface
Mounting location	Ceiling
Equipped with lamp	Yes
Product remark	Available from September 2019
Mercury content	0.0 mg

Capabilities

Dimmable	No
Type of connection	Terminal, 3-Pole (L, N, PE)
Holder designation	G13

Certificates & standards

Protection class	I
Type of protection	IP65
Standards	CE/EAC/REACH/RoHS
Energy clas. of compatible lamps	A++/A+/A

EQUIPMENT / ACCESSORIES

– SubstiTUBE STAR PC EM are delivered with the product

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075303942	Folding carton box 1	77 mm x 71 mm x 1265 mm	1324.00 g	6.92 dm ³
4058075303959	Shipping carton box 9	1280 mm x 225 mm x 245 mm	13189.00 g	70.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.