

LEDiving SX | Slim series



Product family features

- Spot beam patterns
- Powerful far and near field illumination up to 370 m
- Slim design
- Premium OSRAM quality
- Robust and compact design with long lifetime of up to 5,000 h thanks to integrated driver and thermal management system


Product datasheet

Technical data

Electrical data

Nominal voltage	12/24 V
Nominal wattage	30 W

Dimensions & weight



Length	350.0 mm
Product weight	700.00 g

Country specific categorizations

Order reference	LEDDL106-SP 12/
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899595439		Folding carton box 1	387 mm x 137 mm x 89 mm	4.72 dm ³	883.00 g
4052899595446		Shipping carton box 4	407 mm x 296 mm x 208 mm	25.06 dm ³	4072.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Detailed guarantee terms can be found at www.osram.com/am-guarantee.
Driving lights must be installed in pairs for 12/24 V-vehicles.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
