

3886X

ORIGINAL MINIXEN | Signal lamps for cars and motorcycles



Areas of application

- Interior lighting and reading lights

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data



Electrical data

Power input	6 W
Nominal voltage	12.0 V
Nominal wattage	6.00 W
Power input tolerance	±10 %
Test voltage	13.5 V

Photometrical data

Luminous flux	80 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	27.4 mm
Diameter	9 mm
Product weight	1.96 g

Lifespan

Lifespan B3	400 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation)	BA9s
-----------------------------	------

Certificates & standards

ECE category	-
--------------	---

Country specific categorizations

Product datasheet

Order reference	3886X 6W 12V BA
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321095787	OSRA3886X	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321095787	3886X	Unpacked 1	25 mm x 10 mm x 10 mm	0.00 dm ³	1.00 g
4008321095794	3886X	Folding carton box 10	25 mm x 46 mm x 117 mm	0.13 dm ³	21.00 g
4008321095800	3886X	Shipping carton box 50	148 mm x 55 mm x 115 mm	0.94 dm ³	173.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.