

2886X

ORIGINAL MINIXEN | Signal lamps for cars and motorcycles



Areas of application

- Interior lighting and reading lights

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data


Electrical data

Power input	6 W	
Nominal voltage	12.0 V	
Nominal wattage	6.00 W	
Power input tolerance	±10 %	
Test voltage	13.5 V	

Photometrical data

Luminous flux	85 lm
Luminous flux tolerance	±20 %

Dimensions & weight





₩2,1x9,5d IEC 7004-91 DIN 49632 T 2

IEC 7005-91 DIN 49642 T 4

Length	26.8 mm
Diameter	10.0 mm
Product weight	1.35 g

Lifespan

Lifespan B3	400 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation) W2.1x9.5d

Certificates & standards

Country specific categorizations

Order reference	2886X

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321094667	OSRA2886X	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321094667	2886X	Unpacked 1	24 mm x 10 mm x 10 mm	0.00 dm ³	2.00 g
4008321094674	2886X	Folding carton box 10	21 mm x 46 mm x 114 mm	0.11 dm³	24.00 g
4008321094681	2886X	Shipping carton box 50	148 mm x 55 mm x 115 mm	0.94 dm³	149.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.