

2841

ORIGINAL | Lamps with glass wedge bases



Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights
- Interior lighting and reading lights
- Instrument and switch lighting

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data


Electrical data

Power input	4 W
Nominal voltage	24.0 V
Nominal wattage	3.00 W
Power input tolerance	±15 %
Test voltage	28.0 V

Photometrical data

Luminous flux	22 lm
Luminous flux tolerance	±30 %

Dimensions & weight



Length	26.8 mm
Diameter	10.0 mm
Product weight	1.30 g

Lifespan

Lifespan B3	500 h
Lifespan Tc	5000 h

Additional product data

Base (standard designation)	W2.1x9.5d
-----------------------------	-----------

Certificates & standards

ECE category	W3W
--------------	-----

Country specific categorizations

Product datasheet

Order reference	2841 3W24VW2,1X
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4008321094728	OSRA2841	-	4739288	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321094728	2841	Unpacked 1	22 mm x 10 mm x 12 mm	0.00 dm ³	2.00 g
4008321094735	2841	Folding carton box 10	28 mm x 45 mm x 114 mm	0.14 dm ³	22.60 g
4008321094742	2841	Shipping carton box 50	148 mm x 55 mm x 115 mm	0.94 dm ³	147.40 g
4050300926025	2841	Blister 2	81 mm x 12 mm x 53 mm	0.05 dm ³	5.00 g
4008321140388	2841	Shipping carton box 20	117 mm x 106 mm x 103 mm	1.28 dm ³	114.67 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.