

2845

ORIGINAL | Lamps with glass wedge bases



Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights
- Interior lighting and reading lights
- Instrument and switch lighting

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts

Technical data


Electrical data

Power input	7 W
Nominal voltage	24.0 V
Nominal wattage	5.00 W
Power input tolerance	±10 %
Test voltage	28.0 V

Photometrical data

Luminous flux	50 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	26.8 mm
Diameter	10.0 mm
Product weight	1.30 g

Lifespan

Lifespan B3	800 h
Lifespan Tc	3000 h

Additional product data

Base (standard designation)	W2.1x9.5d
-----------------------------	-----------

Certificates & standards

ECE category	W5W
--------------	-----

Country specific categorizations

Product datasheet

Order reference	2845 5W 24V W2.
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300891552	OSRA2845	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321139962	2845	Blister 2	95 mm x 11 mm x 41 mm	0.04 dm ³	7.60 g
4008321139979	2845	Shipping carton box 20	108 mm x 92 mm x 123 mm	1.22 dm ³	118.00 g
4050300891552	2845	Unpacked 1	25 mm x 12 mm x 14 mm	0.00 dm ³	3.67 g
4050300891569	2845	Folding carton box 10	112 mm x 37 mm x 41 mm	0.17 dm ³	20.00 g
4008321094773	2845	Shipping carton box 50	148 mm x 55 mm x 115 mm	0.94 dm ³	145.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.