

9007

OSRAM ORIGINAL LINE | Halogen headlight lamps for cars



Areas of application

- Headlight

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Original spare parts



Technical data

Electrical data


Power input	70 / 60 W ¹⁾
Nominal voltage	12.8 V
Nominal wattage	65/55 W
Test voltage	12.8 V

¹⁾ Maximum

Photometrical data

Luminous flux	1000 lm
Luminous flux tolerance	±10 / ±10 %

Dimensions & weight



Length	95.0 mm
Diameter	16.0 mm
Product weight	34.00 g

Lifespan

Lifespan B3	250 h
Lifespan Tc	500 h ¹⁾

¹⁾ B50 = average lifespanExplanation:1-filament lamp e. g. 100 2-filament lamp e. g. 100/300

Additional product data

Base (standard designation)	PX29t
-----------------------------	-------

Certificates & standards

ECE category	HB5
--------------	-----

Country specific categorizations

Order reference	9007
-----------------	------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300148816	9007	Folding carton box 1	111 mm x 46 mm x 51 mm	0.26 dm ³	47.00 g
4050300148823	9007	Bundle 10	98 mm x 119 mm x 249 mm	2.90 dm ³	462.00 g
4050300148830	9007	Shipping carton box 200	550 mm x 395 mm x 250 mm	54.31 dm ³	9250.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.