# **PHILIPS** Lighting

# MASTER TL5 High Output

## MASTER TL5 HO 49W/865 SLV/40

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

#### **Product data**

General Information				
Cap-Base	G5 [ G5]			
Bulb Shape	T5 [ 16 mm (T5)]			
Life To 50% Failures Preheat (Nom)	30000 h   na [ Not Applicalbe]   High Output   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %			
Features	na [ Not Applicalbe]			
System Description	High Output   99 %   99 %   99 %   99 %			
LSF Preheat 2000 h Rated	na [ Not Applicalbe]   High Output   99 %   99 %   99 %   99 %   99 %   99 %   99 %   99 %			
LSF Preheat 4000 h Rated	99 %			
LSF Preheat 6000 h Rated	99 %			
LSF Preheat 8000 h Rated	99 %			
LSF Preheat 16000 h Rated	High Output   99 %   99 %   99 %   99 %   99 %   99 %   865 [ CCT of 6500K]			
LSF Preheat 20000 h Rated	84 %			
Light Technical				
Color Code	865 [ CCT of 6500K]			
Luminous Flux (Nom)	4550 lm			
Luminous Flux (Rated) (Nom)	4075 lm			
Color Designation	Cool Daylight			
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	92 lm/W			

Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	83 lm/W
Color Rendering Index (Max)	85
Color Rendering Index (Min)	80
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %
Operating and Electrical	
Power (Rated) (Nom)	49.2 W
Lamp Current (Nom)	0.255 A


### MASTER TL5 High Output

Temperature			
Design Temperature (Nom)	35 °C		
Controls and Dimming			
Controls and Dimining			
Dimmable	Yes		
Mechanical and Housing			
Cap-Base Information	Green Plate		
Approval and Application			
Energy Efficiency Label (EEL)	A+		
Mercury (Hg) Content (Nom)	1.4 mg		
Energy Consumption kWh/1000 h	54 kWh		

Product Data			
Full product code	871150064389655		
Order product name	MASTER TL5 HO 49W/865 SLV/40		
EAN/UPC - Product	8711500643896 927927586555		
Order code			
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	40		
Material Nr. (12NC)	927927586555		
Net Weight (Piece)	128.700 g		
ILCOS Code	FDH-49/65/1B-L/P-G5-16/1450		

#### **Dimensional drawing**

Product	D	Α	В	В	С	
---------	---	---	---	---	---	--



TL5 HO 49W/865



© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, December 21 - data subject to change