

PRODUCT DATASHEET

LEDinestra 300 mm 27 3.2 W/2700 K S14d

LEDinestra® | Tubular LED lamps



Areas of application

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Good color rendering

Product features

- LED alternative to tubular incandescent lamps
- Uniform illumination
- Mercury-free lamps
- Bulb made from glass



TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Nominal wattage | 3.2 W |
| Construction wattage | 3.20 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 27 W |
| Nominal current | 29 mA |
| Type of current | AC |
| Inrush current | 5.74 mA |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp no. on circuit break. 10 A (B) | 80 |
| Max. lamp no. on circuit break. 16 A (B) | 130 |
| Total harmonic distortion | 171 % |
| Power factor λ | 0.49 |

Photometrical data

| | |
|---|------------|
| Luminous flux | 275 lm |
| Nominal useful luminous flux 90° | 275 lm |
| Luminous efficacy | 85 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcn |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | 0.1 |
| Stroboscope effect metric (SVM) | 0.1 |



Light technical data

| | |
|------------------------------------|----------|
| Beam angle | 200 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |
| Rated beam angle (half peak value) | 200.00 ° |

Dimensions & Weight



| | |
|------------------|-----------|
| Overall length | 300.00 mm |
| Diameter | 29.00 mm |
| Maximum diameter | 29 mm |
| Product weight | 75.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|------------|
| Ambient temperature range | 0...+30 °C |
| Maximum temperature at tc test point | 50 °C |

Lifespan

| | |
|-------------------------------------|---------|
| Lifespan | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of serv | 0.70 |
| Rated lamp survival factor at 6,000 | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|--|
| Base (standard designation) | S14d |
| Mercury content | 0.0 mg |
| Design / version | Frosted |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--|-----------------|
| Energy efficiency class | F ¹⁾ |
| Energy consumption | 4.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LEDINES 30CM 3, |
|-----------------|-----------------|

LOGISTICAL DATA



| | |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|--------------|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | S14d |
| Connected light source (CLS) | No |
| Color-tunable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0.00 W |
| Networked standby power for CLS | 0.00 W |
| Claim of equivalent power | Yes |
| Length | 300.00 mm |
| Height | 29.00 mm |
| Width | 29.00 mm |
| Chromaticity coordinate x | 0,458 |
| Chromaticity coordinate y | 0,410 |

| | |
|--|------------|
| R9 Colour rendering index | 14.5 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.49 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 522910 |
| Model number | AC33893 |

DOWNLOAD DATA

| DOWNLOAD DATA | |
|---|-------------------------------|
|  | Declarations Of Conformity CE |
|  | LDT file (Eulumdat) |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075607118 | Folding box 1 | 33 mm x 50 mm x 307 mm | 113.00 g | 0.50 dm ³ |
| 4058075607125 | Shipping box 10 | 370 mm x 215 mm x 155 mm | 1332.00 g | 12.33 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.