



# PRODUCT DATA SHEET

## SL-Pro110



# SL-Pro110

## PRODUCT DESCRIPTION

The compact Ledlenser SL Pro110 not only fits in any pocket, it also suits any budget. It may be streamlined down to only the most necessary size and features, but one thing remains unchanged: the extraordinary Ledlenser quality. This power LED will impress you with a bright beam that reaches up to 100 metres<sup>1</sup> to illuminate even the smallest corners. Thanks to its robust aluminium housing, this torch is protected even from rain. So much light for such a low price.

- Compact price–performance champion weighing just 67 g
- More than 100 lm<sup>1</sup> of lighting power with impressive burn time
- Focused on the essentials: maximum operability and solid quality finish
- The robust aluminium housing protects against scratches and splashing water
- Ledlenser's well-known LED quality provides a beam distance of up to 100 metres<sup>1</sup>

### TECHNICAL DATA

Length [mm]	107
Head diameter [mm]	24
Tube diameter [mm]	19
Weight incl. batteries [g]	67
Weight without batteries [g]	45
Focus function	No
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

### POWER SUPPLY

Power source type	Battery
Battery quantity	1
Battery type	Alkaline
Battery description	Mignon (AA) 1.5V
Rechargeable	No
Energy modes	Energy Saving
Usable batteries	AA NiMH 1.2V

### FURTHER SPECIFICATIONS

IP class	IPX4
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

### LIGHT FUNCTIONS

Power

### LIGHT SOURCE

Amount LEDs	1
LED type	Power LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

### LEDLENSER VALUES

Energy Saving	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]		100		
Beam distance <sup>1</sup> [m]		100		
Run time <sup>1</sup> [h]		7		

### SWITCH

End Cap Switch

# SL-Pro110

## PACKAGING AND LOGISTICS



### PACKAGING INFORMATION

Type of packaging	Test It Blister
Scope of delivery	1 set of batteries, Hand strap
Item No.	501066
Customs tariff number	85131000
Color	silver
MSRP price (€)	14.90

### SINGLE PACKAGE

Dimensions W x H x D [cm]	11.2 x 20.5 x 3.8
Gross weight [g]	137
GTIN-13	4058205008891

### INNER CARTON

Unit	6
Dimensions W x D x H [cm]	35.2 x 21.5 x 12.5
Gross weight [g]	1200
GTIN-13	4058205008907

### EXPORT CARTON

Unit	24
Dimensions W x D x H [cm]	45 x 37 x 28
Gross weight [kg]	6
GTIN-13	4058205008914

# SL-Pro110

## ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	MSRP
Battery	500980	4x AA Alkaline Ionic	3.49 €

# — SL-Pro 110

## PRODUCT SERIES

### The Lellenser Solidline-Series

#### High quality, low prices.

Solidline products are specifically designed for frugal flashlight and headlamp aficionados looking for compact basic equipment with sophisticated features without compromising quality. This closes the gap between our premium product target group, filling a very promising, new price segment.

---

## FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Luminous flux (lumen/lm) or maximum beam distance (in meters/m) is measured using the setting specified in the table or text when switching on with a set of fresh alkaline batteries. If no brightness level is named specifically, the values refer to the brightest possible setting. These are average values that may deviate by +/-15 % in individual instances in accordance with chip and battery. The average lighting duration (hours/h), measured in the relevant setting as given in the table or text, down to a luminous flux of 1 lumen. If no brightness level is named specifically, the values refer to the Low Power function, or if not present, to the lowest possible setting.