

COOL BLUE BOOST -

Hyper blue light for off-road use



Hyper blue

For fatigue-free and comfortable driving compared to standard halogen lamps



Up to 5,000 K

High contrast and most stylish look on the road



Up to 50% more light

For better visibility and shorter reaction times compared to other blue coated halogen lamps



The hyper blue halogen light with up to 5,000 K

COOL BLUE BOOST convinces with hyper blue halogen light and high color temperatures of up to 5,000 K. The lamps generate up to 50% more light compared to other blue coated halogen lamps. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product datasheet

Technical data

Product information

| | |
|---|------------------------|
| Order reference | 62210CBB |
| Product type (off-road vs. on-road) | Off-road \pm H7 |
| Application (Category and Product specific) | Halogen headlight lamp |

Electrical data


| | |
|-----------------|--------------------|
| Power input | 73 W ¹⁾ |
| Nominal voltage | 12.0 V |
| Nominal wattage | 80.00 W |
| Test voltage | 13.2 V |

¹⁾ Maximum

Photometrical data

| | |
|-------------------------|------------|
| Luminous flux | 900 lm |
| Luminous flux tolerance | \pm 15 % |
| Color temperature | 3200 K |

Dimensions & weight



| | |
|----------------|---------|
| Diameter | 10.7 mm |
| Product weight | 12.50 g |
| Length | 59.0 mm |

Lifespan

| | |
|-------------|-------|
| Lifespan B3 | 200 h |
| Lifespan Tc | 400 h |

Additional product data

Product datasheet

| | |
|-----------------------------|-------|
| Base (standard designation) | PX26d |
|-----------------------------|-------|

Capabilities

| | |
|------------|-----|
| Technology | HAL |
|------------|-----|

Certificates & standards

| | |
|--------------|---|
| ECE category | - |
|--------------|---|

Country specific categorizations




| | |
|-----------------|----------|
| Order reference | 62210CBB |
|-----------------|----------|

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4052899439801 | COOL BLUE BOOST ≙ H7 | Hard Cover Box 2 | 114 mm x 49 mm x 106 mm | 0.59 dm ³ | 117.00 g |
| 4062172059336 | COOL BLUE BOOST ≙ H7 | Shipping carton box 10 | 268 mm x 126 mm x 125 mm | 4.22 dm ³ | 670.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File |
|--|
|  Brochures Flyer Cool Blue Boost (EN) |
|  Brochures Flyer Cool Blue Boost Jeep Version (EN) |
|  360 Degree Image COOL BLUE BOOST H7 62210CBB |

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Product datasheet

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM