

# LEDDriving HL INTENSE H4/H19



**Up to +350% more brightness**

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112



**Very compact LED replacement for conventional H4H19 high and low beam lamps (2in1)**

Reduced glaring thanks to an optimized light distribution



**Cool White color temperature of 6,000 K**

Better visibility thanks to daylight effect



**5-year OSRAM guarantee**

For precise conditions, please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

## Product datasheet



### OSRAM's highest performing LED off-road retrofit lamp

With up to +350% more brightness (compared to ECE R112) and a very compact LED replacement of conventional H7/H18 and H4/H19 high and low beam lamps, the LEDDriving HL INTENSE is OSRAM's highest performing LED off-road retrofit lamp ever! This LED retrofit lamp offers OSRAM top technology beam pattern as well as an easy installation with a wide OSRAM range of suitable accessories. Top thermal management technology with integrated active cooling – a high speed fan ensures maximized heat dissipation for more powerful performances. Also premium OSRAM quality, manufactured in a certified OSRAM production plant in Italy, and a 5-year guarantee as well as a long service life. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). The LED high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a color temperature of 6,000K. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for an even wider range of car models. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

## Technical data

### Product information

Order reference	64193DWINT
Product type (off-road vs. on-road)	Off-road $\pm$ H4/H19
Application (Category and Product specific)	Mainly used for Low Beam, High Beam

### Electrical data

Power input	25 / 21.0 W
Nominal voltage	12.0 V
Nominal wattage	27/23 W
Test voltage	13.2 V
Power input tolerance	$\pm$ 15 %

### Photometrical data

Luminous flux	1900/1350 lm
Luminous flux tolerance	$\pm$ 20 %
Color temperature	6000 K
Light color LED	Cool white

### Dimensions & weight

Length	87.4 mm
Diameter	18.5 mm
Product weight	76.00 g

### Lifespan

Lifespan Tc	5000 h
Guarantee	5 years

### Additional product data

Base (standard designation)	P43t / PU43t-3
-----------------------------	----------------

### Capabilities

Technology	LED
------------	-----

### Country specific categorizations

Order reference	64193DWINT
-----------------	------------

### Environmental information

## Product datasheet

### Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)




Date of Declaration	07-10-2022
Primary Article Identifier	4062172306454
Declaration No. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172306454	≅ H4/H19	Folding carton box 2	136 mm x 56 mm x 162 mm	1.23 dm <sup>3</sup>	220.00 g
4062172306461	≅ H4/H19	Shipping carton box 8	240 mm x 148 mm x 182 mm	6.46 dm <sup>3</sup>	1006.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 User instruction LEDriving HL INTENSE
 Brochures LEDriving Retrofits - Exchange overview (EN)
 Brochures 618438_LEDriving RETROFIT application overview (EN)

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



